

**ANY CHASSIS PERMITTED
WHEELIE BARS PERMITTED
ANY TRANSMISSION PERMITTED
DUAL POWER ADDERS (PROHIBITED)**

TIRES ALLOWED:

**(315 DOT) (3062R) (3362R) (33-10.5W Bias Ply)
Front Overhang Max 45 inches from center of spindle**

**** -50 LBS for stock suspension
(suspension for year make model car only)**

**BB NOS No Weight Limit (5.00 BORE ENGINES)
BB NOS 2250 LBS (OVER 5.00 BORE ENGINES)**

**SB SINGLE TURBO 2400 LBS
SB TWIN TURBO 2400 LBS (Stock Bore Space)
SB TWIN TURBO 2500 LBS (4.500 Non-Stock Bore Space)
SB TWIN TURBO (4.600+) 2550 LBS
SB TWIN TURBO (HEMI) 2600 LBS
-150 lbs. for SB TWIN TURBO (Cast Block / Cast Head)
-150 lbs. for SB TWIN TURBO (Inline Head)
(Cant Combine with Cast Block / Cast Head Rule)**

**SB PROCHARGER 2400 LBS
(-50 lbs. for Cast Block / Cast Head Combo)**

**BB PROCHARGER 2550 LBS
(-50 lbs. for Cast Block / Cast Head Combo)**

**BB TWIN TURBO 2750 LBS
BB TWIN TURBO (4.840 Stock Bore Space) 2700 LBS
(Wedge Engine Only)**

**BB Single Turbo 2450 LBS
4 cyl. combos 1950 LBS (Production Engines Only)
6 cyl. combos 2500 LBS (Production Engines Only)**

**BB ROOTS BLOWER 2425 LBS
BB SCREW 2785 LBS
SB SCREW WEDGE 2300 LBS (4.400 Bore Space)
SB SCREW WEDGE 2350 LBS (4.500 / 4.600 Bore Space)
SB SCREW HEMI 2625 LBS**